

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address COMMISSIONER FOR PATENTS FO Box 1430 Alexandra, Virginia 22313-1450 www.tepto.gov

| APPLICATION NO.  | FILING DATE | FIRST NAMED INVENTOR | ATTORNEY DOCKET NO. | CONFIRMATION NO. |
|--|-------------|----------------------|---------------------|------------------|
| 10/600,571   | 06/23/2003  | Masao Hori           | HARA-072-046        | 9645             |
| 26374 7559 12102908<br>KUBOVCIK & KUBOVCIK<br>SUITE 1105<br>1215 SOUTH CLARK STREET<br>ARLINGTON, VA 22202 |             |                      | EXAMINER            |                  |
|  |             |                      | NGUYEN, TU MINH     |                  |
|  |             |                      | ART UNIT            | PAPER NUMBER     |
| THE HOTOIT   | , 111 22202 |                      | 3748                |                  |
|  |             |                      |                     |                  |
|  |             |                      | MAIL DATE           | DELIVERY MODE    |
|  |             |                      | 12/10/2008          | PAPER            |

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

## Application No. Applicant(s) 10/600,571 HORI ET AL. Office Action Summary Examiner Art Unit TU M. NGUYEN 3748 -- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --Period for Reply A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS. WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION. Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication. If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication - Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b). Status 1) Responsive to communication(s) filed on 07 November 2008. 2a) This action is FINAL. 2b) This action is non-final. 3) Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under Ex parte Quayle, 1935 C.D. 11, 453 O.G. 213. Disposition of Claims 4) Claim(s) 17-19.21-25 and 29 is/are pending in the application. 4a) Of the above claim(s) is/are withdrawn from consideration. 5) Claim(s) \_\_\_\_\_ is/are allowed. 6) Claim(s) 17-19,21-25 and 29 is/are rejected. 7) Claim(s) \_\_\_\_\_ is/are objected to. 8) Claim(s) \_\_\_\_\_ are subject to restriction and/or election requirement. Application Papers 9) The specification is objected to by the Examiner. 10) The drawing(s) filed on 23 June 2003 is/are: a) accepted or b) objected to by the Examiner. Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a). Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d). 11) The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152. Priority under 35 U.S.C. § 119 12) Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f). a) All b) Some \* c) None of: Certified copies of the priority documents have been received. 2. Certified copies of the priority documents have been received in Application No. 08/875,577. Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)). \* See the attached detailed Office action for a list of the certified copies not received. Attachment(s) 1) Notice of References Cited (PTO-892) 4) Interview Summary (PTO-413) Paper No(s)/Mail Date. \_\_\_ Notice of Draftsperson's Patent Drawing Review (PTO-948) 5) Notice of Informal Patent Application 3) Information Disclosure Statement(s) (PTO/SB/08)

Paper No(s)/Mail Date \_

6) Other:

## DETAILED ACTION

An Applicant's Request for Continued Examination (RCE) filed on November 7, 2008
has been entered. Per instruction from the RCE, an enclosed Applicant's Amendment has also
been entered. Claims 20, 26-28, and 30-32 have been canceled; and claims 17-18 have been
amended. Overall, claims 17-19, 21-25, and 29 are pending in this application.

## Claim Rejections - 35 USC § 103

- The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all
  obviousness rejections set forth in this Office Action:
  - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior at are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 3. Claims 17-19, 21-25, and 29 are rejected under 35 U.S.C. 103(a) as being unpatentable over Katoh et al. (U.S. Patent 5,402,641) in view Ozawa et al. (U.S. Patent 5,075,276).

Re claim 17, as illustrated in Figures 1 and 5, Katoh et al. disclose a process for purifying exhaust gas from lean burning internal combustion engines using an exhaust gas purifying-use catalyst (6) containing a noble metal (platinum) and a transition metal (copper) (see line 61 of column 3 to line 3 of column 4) and which removes hydrocarbons, carbon monoxide, and nitrogen oxides from the exhaust gas, comprising:

Art Unit: 3748

- providing a gasoline engine (2) of the carburetor type;

- injecting gasoline into a cylinder of the gasoline engine to provide a mixture of air and gasoline having an air-fuel ratio of 13 to 15 and combusting the mixture to form an exhaust gas in a first exhaust gas state (stoichiometric or rich air-fuel ratio) having an exhaust-gas temperature in a range of 350°C to 800°C at an inlet to the catalyst (step 106 with YES answer and step 108) (in step 108, the first exhaust gas state is stoichiometric with an air-fuel ratio of 14.7); wherein the catalyst being obtained by mixing the noble metal and the transition metal with or carrying the noble metal and the transition metal by a fire-resistant inorganic oxide, the fire-resistant inorganic oxide being active alumina (line 62 of column 3);

- contacting the exhaust gas in the first exhaust gas state with the catalyst to remove hydrocarbons, carbon monoxide, and nitrogen oxides from the first exhaust gas and purify the first exhaust gas (see at least Figure 3B and lines 23-28 of column 4);
- injecting gasoline into the cylinder of the gasoline engine to provide a mixture of air and gasoline having an air-fuel ratio of more than 15 to 50 (see lines 25-26 of column 5) and combusting the mixture to form an exhaust gas in a second exhaust gas state (lean air-fuel ratios) having an exhaust-gas temperature being in a range of 200°C to 500°C at the inlet to the catalyst (step 106 with NO answer and step 110); and
- contacting the exhaust gas in the second exhaust gas state with the catalyst to remove hydrocarbons, carbon monoxide, and nitrogen oxides from the second exhaust gas and purify the second exhaust gas (see at least Figure 3A and lines 15-23 of column 4).

Katoh et al., however, fail to disclose that their engine is a gasoline fuel-direct-injection type engine which allows fuel to be directly injected inside a cylinder of the engine; and that an Application/Control Number: 10/600,571

Art Unit: 3748

amount of the noble metal being in a range of 0.01 to 50 g/liter with respect to the catalyst volume, the fire-resistant inorganic oxide having a BET surface area of 50  $\rm m^2/g$  to 200  $\rm m^2/g$  and having a pore diameter of 10 nm to 30 nm.

Katoh et al. disclose the claimed invention except for applying the invention to a gasoline fuel-direct-injection type engine. It would have been obvious to one having ordinary skill in the art at the time the invention was made to apply the invention of Katoh et al. to a gasoline fuel-direct-injection type engine, since the recitation of such amounts to an intended use statement. Note that both "gasoline fuel-direct-injection engine" and "gasoline carburetor-injection engine" generate exhaust gases containing harmful emissions of HC, NOx, soot, CO, and SOx, that require purification before the gases can be released to the atmosphere; and the mere selection of the purification process of Katoh et al. for use in a gasoline fuel-direct-injection engine would be well within the level of ordinary skill in the art.

Ozawa et al. disclose a catalyst adapted to purify hydrocarbons, carbon monoxide, and NOx in the exhaust gas of an internal combustion engine. As indicated on lines 15-62 of column 6, Ozawa et al. teach that their catalyst comprises a catalytically active coating having a platinum metal group and a high surface area support material. The platinum metal group is in a density range of 0.01 to 5 g/liter of the catalyst volume (see line 57 of column 6). The high surface area support material is a fire-resistant inorganic oxide (gamma alumina) having a BET surface area of 50 m²/g to 200 m²/g and having a pore diameter of 10 nm to 30 nm (300 angstrom = 30 nm) (see lines 16-20 of column 6). As depicted in Figure 2, Ozawa et al. further teach that their catalyst has relatively high purification efficiencies of HC, CO, and NOx based on said composition of the catalyst. It would have been obvious to one having ordinary skill in the art at

Application/Control Number: 10/600,571

Art Unit: 3748

the time of the invention was made, to have utilized the density range of platinum and the inorganic oxide taught by Ozawa et al. in the eatalyst of Katoh et al., since the use thereof would have provided a catalyst having high efficiencies in removing HC, CO, and NOx emissions in the exhaust gas.

Re claim 18, in the modified process of Katoh et al., the exhaust gas in the second exhaust gas state (lean air-fuel ratio) forms a more oxidizing, low-temperature atmosphere as compared with the first exhaust gas state (stoichiometric or rich air-fuel ratio).

Re claim 19, in the modified process of Katoh et al., the first exhaust-gas state (stoichiometric or rich air-fuel ratio) is a state at a time of high output of the gasoline engine of a fuel-direct-injection type, and the second exhaust-gas state (lean air-fuel ratio) is a state at a time of low output of the gasoline engine (see at least Figure 13 and lines 24-41 of column 10).

Re claim 21, in the modified process of Katoh et al., the transition metal (copper) is at least one selected from the group consisting of manganese, iron, cobalt, copper, and nickel.

Re claim 22, in the modified process of Katoh et al., the catalyst includes at least one noble metal (platinum) selected from the group consisting of platinum, rhodium, palladium and iridium.

Re claim 23, in the modified process of Katoh et al., the exhaust-gas temperature in the second exhaust-gas state (lean air-fuel ratio) ranges from 200°C to 350°C at the inlet of the catalyst.

Re claim 24, in the modified process of Katoh et al., the catalyst includes platinum and rhodium as the noble metal (see lines 65-66 of column 3).

Art Unit: 3748

Re claim 25, in the modified process of Katoh et al., the catalyst includes at least one of a cerium-oxide powder and a zirconium-oxide powder (see Table 2 and lines 50-62 of column 4 in Ozawa et al.).

Re claim 29, in the modified process of Katoh et al., when the temperature of the exhaust gas at the inlet of the catalyst is higher than 500°C, the catalyst is unable to reduce NOx contained in the exhaust gas that is in the second exhaust gas state (the catalyst in Katoh et al. is unable to reduce NOx from the second (lean) exhaust gas state).

Art Unit: 3748

## Communication

 Any inquiry concerning this communication or earlier communications from the examiner should be directed to Examiner Tu Nguyen whose telephone number is (571) 272-4862.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Mr. Thomas E. Denion, can be reached on (571) 272-4859. The fax phone number for the organization where this application or proceeding is assigned is (571) 273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <a href="http://pair-direct.uspto.gov">http://pair-direct.uspto.gov</a>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

/Tu M. Nguyen/

TMN Tu M. Nguyen

December 7, 2008 Primary Examiner

Art Unit 3748